

SAFETY DATA SHEET

1. Identification

Product identifier: NAPA Mac's 1397 Belt Dressing

Other means of identification

SDS number: RE1000036034

Recommended restrictions

Product use: Lubricant

Restrictions on use: Not known.

Manufacturer/Importer/Distributor Information

Manufacturer

Company Name: NAPA BALKAMP
Address: 1601 Whitaker Rd
INDIANAPOLIS, IN 46168
Telephone: 317-837-2800
Fax:

Emergency telephone number: 1-866-836-8855

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable aerosol Category 1

Health Hazards

Skin Corrosion/Irritation Category 2
Serious Eye Damage/Eye Irritation Category 2A
Skin sensitizer Category 1
Specific Target Organ Toxicity -
Single Exposure Category 3¹.
Aspiration Hazard Category 1

Target Organs

1. Narcotic effect.

Environmental Hazards

Acute hazards to the aquatic
environment Category 2
Chronic hazards to the aquatic
environment Category 3

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: Extremely flammable aerosol.
Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.
May cause drowsiness or dizziness.
May be fatal if swallowed and enters airways.
Toxic to aquatic life.
Harmful to aquatic life with long lasting effects.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing should not be allowed out of the workplace. Use only outdoors or in a well-ventilated area. Avoid release to the environment.

Response: IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. Call a POISON CENTER/doctor if you feel unwell. Specific treatment (see on this label). Wash contaminated clothing before reuse.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
2-Propanone	67-64-1	20 - <50%
Propane	74-98-6	10 - <20%
Butane	106-97-8	10 - <20%
Solvent naphtha (petroleum), light aliph.	64742-89-8	10 - <20%
Heptane	142-82-5	5 - <10%
Heptane, branched, cyclic and linear	426260-76-6	5 - <10%
Naphtha (petroleum), hydrotreated light	64742-49-0	5 - <10%
Naphtha (petroleum), heavy alkylate	64741-65-7	5 - <10%
Maleic Anhydride Modified Liquid Polyisoprene	841251-34-1	1 - <5%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Call a physician or poison control center immediately. Rinse mouth. Never give liquid to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Inhalation:	Move to fresh air.
Skin Contact:	Get medical attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

Symptoms:	No data available.
Hazards:	No data available.

Indication of immediate medical attention and special treatment needed

Treatment:	No data available.
-------------------	--------------------

5. Fire-fighting measures

General Fire Hazards:	Use water spray to keep fire-exposed containers cool. Fight fire from a protected location. Move containers from fire area if you can do so without risk.
------------------------------	---

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical:	Vapors may travel considerable distance to a source of ignition and flash back.
--	---

Special protective equipment and precautions for firefighters

Special fire fighting procedures:	No data available.
Special protective equipment for fire-fighters:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:	Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.
Methods and material for containment and cleaning up:	Absorb spill with vermiculite or other inert material, then place in a container for chemical waste.
Notification Procedures:	Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage

Precautions for safe handling: Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid contact with skin. Avoid contact with eyes, skin, and clothing.

Conditions for safe storage, including any incompatibilities: Store locked up. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Aerosol Level 3

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values		Source
2-Propanone	STEL	1,000 ppm	2,400 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	PEL	1,000 ppm	2,400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	250 ppm		US. ACGIH Threshold Limit Values (03 2015)
	TWA	750 ppm	1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL	500 ppm		US. ACGIH Threshold Limit Values (03 2015)
	REL	250 ppm	590 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
Propane	REL	1,000 ppm	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	1,000 ppm	1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	1,000 ppm	1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Butane	REL	800 ppm	1,900 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	STEL	1,000 ppm		US. ACGIH Threshold Limit Values (03 2018)
	TWA	800 ppm	1,900 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Solvent naphtha (petroleum), light aliph.	REL	100 ppm	400 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	TWA	100 ppm	400 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	PEL	100 ppm	400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (03 2016)
Naphtha (petroleum), hydrotreated light	PEL	100 ppm	400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (03 2016)
	REL	100 ppm	400 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	TWA	100 ppm	400 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Heptane	TWA	400 ppm	1,600 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	REL	85 ppm	350 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	STEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	400 ppm		US. ACGIH Threshold Limit Values (02 2012)
	STEL	500 ppm		US. ACGIH Threshold Limit Values (02 2012)
	Ceil_Time	440 ppm	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
Naphtha (petroleum), heavy alkylate	PEL	100 ppm	400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	100 ppm	400 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	REL	100 ppm	400 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
Distillates (petroleum), hydrotreated heavy naphthenic	TWA	400 ppm	1,600 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	PEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Distillates (petroleum), hydrotreated heavy naphthenic - Mist.	REL		5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	STEL		10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA		5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Distillates (petroleum).	Ceil_Time		1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)

hydrotreated heavy naphthenic				
Distillates (petroleum), hydrotreated heavy naphthenic - Inhalable fraction.	TWA	5 mg/m3		US. ACGIH Threshold Limit Values (03 2014)
Distillates (petroleum), hydrotreated heavy naphthenic	REL	350 mg/m3		US. NIOSH: Pocket Guide to Chemical Hazards (2010)
Benzene, methyl-	STEL	150 ppm	560 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	REL	100 ppm	375 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	100 ppm	375 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	Ceiling	300 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	TWA	20 ppm		US. ACGIH Threshold Limit Values (2008)
	TWA	200 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	MAX. CONC	500 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	STEL	150 ppm	560 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
Benzene	REL	0.1 ppm		US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	1 ppm		US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	Ceiling	25 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	TWA	0.5 ppm		US. ACGIH Threshold Limit Values (2008)
	STEL	2.5 ppm		US. ACGIH Threshold Limit Values (2008)
	STEL	5 ppm		US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	OSHA_AC T	0.5 ppm		US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	TWA	10 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	MAX. CONC	50 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	STEL	5 ppm		US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	1 ppm		US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	STEL	1 ppm		US. NIOSH: Pocket Guide to Chemical Hazards (2005)
Benzene, (1-methylethyl)-	REL	50 ppm	245 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	50 ppm		US. ACGIH Threshold Limit Values (2008)
	PEL	50 ppm	245 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 ppm	245 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	1 ppm		US. ACGIH Notice of Intended Changes (NIC) to Threshold Limit Values (03 2018)
Benzene, ethyl-	STEL	125 ppm	545 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	STEL	125 ppm	545 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm	435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	20 ppm		US. ACGIH Threshold Limit Values (12 2010)
Hexane	TWA	50 ppm	180 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	PEL	500 ppm	1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	REL	50 ppm	180 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	50 ppm		US. ACGIH Threshold Limit Values (2008)
Cyclohexane	TWA	100 ppm		US. ACGIH Threshold Limit Values (2008)
	TWA	300 ppm	1,050 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	REL	300 ppm	1,050 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	300 ppm	1,050 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
2-Propanone (acetone: Sampling time: End of shift.)	25 mg/l (Urine)	ACGIH BEL (03 2015)
Benzene, methyl- (toluene: Sampling time: End of shift.)	0.03 mg/l (Urine)	ACGIH BEL (03 2013)
Benzene, methyl- (o-Cresol, with hydrolysis: Sampling time: End of shift.)	0.3 mg/g (Creatinine in urine)	ACGIH BEL (03 2013)
Benzene, methyl- (toluene: Sampling time: Prior to last shift of work week.)	0.02 mg/l (Blood)	ACGIH BEL (03 2013)
Benzene (S-Phenylmercapturic acid: Sampling time: End of shift.)	25 µg/g (Creatinine in urine)	ACGIH BEL (03 2013)
Benzene (t,t-Muconic acid: Sampling time: End of shift.)	500 µg/g (Creatinine in urine)	ACGIH BEL (03 2013)
Benzene, ethyl- (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)
Hexane (2,5-Hexanedion, without hydrolysis: Sampling time: End of shift.)	0.5 mg/l (Urine)	ACGIH BEL (03 2018)

Appropriate Engineering Controls No data available.

Individual protection measures, such as personal protective equipment

General information: Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection
Hand Protection: No data available.

Other: Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.

Hygiene measures: Observe good industrial hygiene practices. Avoid contact with eyes. When using do not smoke. Wash contaminated clothing before reuse. Avoid contact with skin. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state: liquid

Form: Spray Aerosol

Color: No data available.

Odor: No data available.

Odor threshold: No data available.

pH: No data available.

Melting point/freezing point: No data available.

Initial boiling point and boiling range: No data available.

Flash Point: Estimated -104.44 °C

Evaporation rate: No data available.

Flammability (solid, gas): No data available.

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%): Estimated 9.5 %(V)

Flammability limit - lower (%): Estimated 1.9 %(V)

Explosive limit - upper (%): No data available.

Explosive limit - lower (%): No data available.

Vapor pressure: Estimated 2,068 - 3,447 hPa (20 °C)

Vapor density: No data available.

Density: No data available.

Relative density: No data available.

Solubility(ies)

Solubility in water: No data available.

Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	No data available.
Hazardous Decomposition Products:	No data available.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product:	Not classified for acute toxicity based on available data.
-----------------	--

Specified substance(s):

2-Propanone	LD 50 (Rat): 5,800 mg/kg
Solvent naphtha (petroleum), light aliph.	LD 50 (Rat): > 5,000 mg/kg
Heptane	LD 50 (Rat): > 5,000 mg/kg
Heptane, branched, cyclic and linear	LD 50: > 2,000 mg/kg
Naphtha (petroleum), hydrotreated light	LD 50 (Rat): > 5,000 mg/kg

Naphtha (petroleum),
heavy alkylate LD 50: > 2,000 mg/kg

Maleic Anhydride
Modified Liquid
Polyisoprene LD 50: > 2,000 mg/kg

Dermal

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

2-Propanone LD 50 (Rabbit): > 7,426 mg/kg

Solvent naphtha
(petroleum), light aliph. LD 50 (Rabbit): > 2,000 mg/kg

Heptane LD 50 (Rabbit): > 2,000 mg/kg

Heptane, branched,
cyclic and linear LD 50: > 2,000 mg/kg

Naphtha (petroleum),
hydrotreated light LD 50 (Rabbit): > 3,750 mg/kg

Naphtha (petroleum),
heavy alkylate LD 50: > 2,000 mg/kg

Maleic Anhydride
Modified Liquid
Polyisoprene LD 50: > 2,000 mg/kg

Inhalation

Product: ATEmix: 65.21 mg/l

Repeated dose toxicity

Product: No data available.

Specified substance(s):

2-Propanone NOAEL (Rat(Male), Oral, 13 Weeks): 10,000 ppm(m) Oral Experimental result, Key study

Propane NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation Experimental result, Key study
LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation Experimental result, Key study

Butane LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation Experimental result, Key study
NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation Experimental result, Key study

Solvent naphtha
(petroleum), light aliph. NOAEL (Mouse, Rat(Female, Male), Inhalation, 107 - 113 Weeks): 1,402 mg/m3 Inhalation Experimental result, Key study
NOAEL (Rat(Female, Male), Dermal, 5 - 28 d): 3,750 mg/kg Dermal Experimental result, Key study
NOAEL (Rat(Female, Male), Dermal, 28 d): > 375 mg/kg Dermal Experimental result, Supporting study

Heptane NOAEL (Rat(Male), Inhalation): 12,470 mg/m3 Inhalation Experimental result, Key study

Naphtha (petroleum),
hydrotreated light LOAEL (Rat(Female, Male), Oral, 13 Weeks): 1,250 mg/kg Oral Read-across based on grouping of substances (category approach), Key study
NOAEL (Rat(Female, Male), Dermal, 28 d): > 375 mg/kg Dermal Experimental result, Supporting study
NOAEL (Rat(Female, Male), Inhalation): 10,000 mg/m3 Inhalation Experimental result, Key study

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

2-Propanone in vivo (Rabbit): Not irritant Experimental result, Supporting study

Solvent naphtha Assessment Non-Irritating
(petroleum), light aliph. in vivo (Rabbit): Irritating Experimental result, Key study

Heptane in vivo (Rabbit): Irritating Read-across based on grouping of substances
(category approach), Key study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

2-Propanone Irritating.
Rabbit, 24 hrs: Minimum grade of severe eye irritant

Solvent naphtha Rabbit: Not irritating
(petroleum), light aliph.

Heptane Rabbit, 24 - 72 hrs: Not irritating

Naphtha (petroleum), Rabbit, 24 - 72 hrs: Not irritating
hydrotreated light

Respiratory or Skin Sensitization

Product: No data available.

Specified substance(s):

2-Propanone Skin sensitization:, in vivo (Guinea pig): Non sensitising

Solvent naphtha Skin sensitization:, in vivo (Guinea pig): Non sensitising
(petroleum), light aliph.

Heptane Skin sensitization:, in vivo (Guinea pig): Non sensitising

Naphtha (petroleum), Skin sensitization:, in vivo (Guinea pig): Non sensitising
hydrotreated light

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specified substance(s):

2-Propanone	Inhalation - vapor: Narcotic effect. - Category 3 with narcotic effects.
Heptane	Narcotic effect. - Category 3 with narcotic effects.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Target Organs

Specific Target Organ Toxicity - Single Exposure: Narcotic effect.

Aspiration Hazard

Product: No data available.

Specified substance(s):

Solvent naphtha (petroleum), light aliph.	May be fatal if swallowed and enters airways.
Heptane	May be fatal if swallowed and enters airways.
Heptane, branched, cyclic and linear	May be fatal if swallowed and enters airways.
Naphtha (petroleum), hydrotreated light	May be fatal if swallowed and enters airways.
Naphtha (petroleum), heavy alkylate	May be fatal if swallowed and enters airways.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

2-Propanone	LC 50 (Oncorhynchus mykiss, 96 h): 5,540 mg/l Experimental result, Key study
Propane	LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study
Butane	LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study
Solvent naphtha (petroleum), light aliph.	LL 50 (Pimephales promelas, 96 h): 8.2 mg/l Experimental result, Key study
Heptane	LC 50 (Mozambique tilapia (Tilapia mossambica), 96 h): 375 mg/l Mortality
Naphtha (petroleum), hydrotreated light	LC 50 (96 h): 8.41 mg/l Experimental result, Key study

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

2-Propanone	LC 50 (Daphnia pulex, 48 h): 8,800 mg/l Experimental result, Key study
Butane	LC 50 (Daphnia sp., 48 h): 69.43 mg/l QSAR QSAR, Key study
Solvent naphtha (petroleum), light aliph.	EC 50 (Daphnia magna, 48 h): 4.5 mg/l Experimental result, Key study NOAEL (Daphnia magna, 48 h): 0.5 mg/l Experimental result, Key study
Heptane	EC 50 (Daphnia magna, 48 h): 1.5 mg/l Experimental result, Key study

Naphtha (petroleum), hydrotreated light EC 50 (Daphnia magna, 48 h): 4.5 mg/l Experimental result, Key study

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Solvent naphtha (petroleum), light aliph. NOAEL (Daphnia magna): 2.6 mg/l Other, Key study

Heptane NOAEL (Oncorhynchus mykiss): 1.284 mg/l QSAR QSAR, Key study

Naphtha (petroleum), hydrotreated light EC 50 (Daphnia magna): 10 mg/l Other, Key study
NOAEL (Daphnia magna): 2.6 mg/l Other, Key study

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

2-Propanone LOAEL (Daphnia magna): 2,212 mg/l Experimental result, Key study
NOAEL (Daphnia magna): 2,212 mg/l Experimental result, Key study

Solvent naphtha (petroleum), light aliph. EC 50 (Daphnia magna): > 40 mg/l Experimental result, Key study

Heptane NOAEL (Daphnia magna): 0.17 mg/l Read-across based on grouping of substances (category approach), Key study
EC 50 (Daphnia magna): 0.23 mg/l Read-across based on grouping of substances (category approach), Key study

Heptane, branched, cyclic and linear NOEC : < 1 mg/l estimation

Naphtha (petroleum), hydrotreated light EC 50 (Daphnia magna): 10 mg/l Experimental result, Key study
NOAEL (Daphnia magna): 2.6 mg/l Experimental result, Key study

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

Specified substance(s):

2-Propanone 90.9 % (28 d) Detected in water. Experimental result, Key study

Propane 100 % (385.5 h) Detected in water. Experimental result, Key study
50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study

Butane 100 % (385.5 h) Detected in water. Experimental result, Key study

Solvent naphtha (petroleum), light aliph. 90.35 % (28 d) Detected in water. Experimental result, Supporting study
77.05 % Detected in water. Experimental result, Supporting study

Heptane 70 % Detected in water. Experimental result, Key study

Naphtha (petroleum), hydrotreated light 90.35 % (28 d) Detected in water. Experimental result, Supporting study

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Specified substance(s):

2-Propanone Haddock, adult, Bioconcentration Factor (BCF): 0.69 Aquatic sediment
Experimental result, Not specified

Solvent naphtha (petroleum), light aliph. Bioconcentration Factor (BCF): 10 - 2,500 Aquatic sediment Estimated by
calculation, Key study

Heptane Bioconcentration Factor (BCF): 552 Aquatic sediment Estimated by
calculation, Key study

Naphtha (petroleum), hydrotreated light Bioconcentration Factor (BCF): 10 - 2,500 Aquatic sediment Estimated by
calculation, Key study

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Naphtha (petroleum), hydrotreated light Log Kow: > 2.4 - < 5.7 23 °C Yes Experimental result, Key study
Log Kow: 2.2 - 5.2 23 °C Yes Experimental result, Key study
Log Kow: 2.2 - 6.1 23 °C Yes Experimental result, Key study

Mobility in soil: No data available.

Known or predicted distribution to environmental compartments

2-Propanone	No data available.
Propane	No data available.
Butane	No data available.
Solvent naphtha (petroleum), light aliph.	No data available.
Heptane	No data available.
Heptane, branched, cyclic and linear	No data available.
Naphtha (petroleum), hydrotreated light	No data available.
Naphtha (petroleum), heavy alkylate	No data available.
Maleic Anhydride Modified Liquid Polyisoprene	No data available.

Other adverse effects: Toxic to aquatic organisms. Harmful to aquatic life with long lasting effects.

13. Disposal considerations

Disposal instructions: Discharge, treatment, or disposal may be subject to national, state, or local laws.

Contaminated Packaging: No data available.

14. Transport information

DOT

UN Number:	UN 1950
UN Proper Shipping Name:	Aerosols, flammable
Transport Hazard Class(es)	
Class:	2.1
Label(s):	—
Packing Group:	II
Marine Pollutant:	No
Environmental Hazards:	No
Marine Pollutant	No
Special precautions for user:	Not regulated.

IMDG

UN Number:	UN 1950
UN Proper Shipping Name:	Aerosols, flammable
Transport Hazard Class(es)	
Class:	2
Label(s):	—
EmS No.:	
Packing Group:	—
Environmental Hazards:	No
Marine Pollutant	No
Special precautions for user:	Not regulated.

IATA

UN Number:	UN 1950
Proper Shipping Name:	Aerosols, flammable
Transport Hazard Class(es):	
Class:	2.1
Label(s):	—
Packing Group:	—
Environmental Hazards:	No
Marine Pollutant	No
Special precautions for user:	Not regulated.

15. Regulatory information

US Federal Regulations

Restrictions on use: Not known.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Benzene	Flammability Cancer Aspiration Eye Blood Skin respiratory tract irritation Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
2-Propanone	lbs. 5000
Propane	lbs. 100
Butane	lbs. 100
Heptane	lbs. 100
Benzene, methyl-	lbs. 1000
Benzene	lbs. 10
Benzene, (1-methylethyl)-	lbs. 5000
Benzene, ethyl-	lbs. 1000
Hexane	lbs. 5000
Cyclohexane	lbs. 1000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard
Immediate (Acute) Health Hazards
Flammable aerosol
Skin Corrosion/Irritation
Serious Eye Damage/Eye Irritation
Skin sensitizer
Specific Target Organ Toxicity - Single Exposure
Aspiration Hazard

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
2-Propanone		
Hexane		

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
2-Propanone	lbs. 5000
Propane	lbs. 100
Butane	lbs. 100
Heptane	lbs. 100
Benzene, methyl-	lbs. 1000
Benzene	lbs. 10
Benzene, (1-methylethyl)-	lbs. 5000
Benzene, ethyl-	lbs. 1000
Hexane	lbs. 5000
Cyclohexane	lbs. 1000

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
2-Propanone	10000 lbs
Propane	10000 lbs
Butane	10000 lbs
Solvent naphtha (petroleum), light aliph.	10000 lbs
Heptane	10000 lbs
Heptane, branched, cyclic and linear	10000 lbs
Naphtha (petroleum), hydrotreated light	10000 lbs
Naphtha (petroleum), heavy alkylate	10000 lbs
Maleic Anhydride Modified Liquid Polyisoprene	10000 lbs
Distillates (petroleum), hydrotreated heavy naphthenic	10000 lbs
Benzene, methyl-	10000 lbs
Benzene	10000 lbs
Benzene, (1-methylethyl)-	10000 lbs
Benzene, ethyl-	10000 lbs
Hexane	10000 lbs
Cyclohexane	10000 lbs

SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3) US State Regulations

US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

Benzene, methyl-	Developmental toxin. 03 2008
Benzene	Developmental toxin. 03 2008
Benzene	Carcinogenic. 05 2011
Benzene	Male reproductive toxin. 03 2008
Benzene, (1-methylethyl)-	Carcinogenic. 05 2011
Benzene, ethyl-	Carcinogenic. 05 2011
Hexane	Male reproductive toxin. 12 2017

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

2-Propanone
Propane
Butane
Solvent naphtha (petroleum), light aliph.
Naphtha (petroleum), hydrotreated light
Heptane
Naphtha (petroleum), heavy alkylate
Distillates (petroleum), hydrotreated heavy naphthenic

US. Massachusetts RTK - Substance List

Chemical Identity

Benzene

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

2-Propanone
Propane
Butane
Solvent naphtha (petroleum), light aliph.
Naphtha (petroleum), hydrotreated light
Heptane
Naphtha (petroleum), heavy alkylate

US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.

International regulations

Montreal protocol

2-Propanone

Stockholm convention

2-Propanone

Rotterdam convention

2-Propanone

Kyoto protocol

Inventory Status:

Australia AICS:	Not in compliance with the inventory.
Canada DSL Inventory List:	On or in compliance with the inventory
Canada NDSL Inventory:	Not in compliance with the inventory.
Ontario Inventory:	Not in compliance with the inventory.
China Inv. Existing Chemical Substances:	On or in compliance with the inventory
Japan (ENCS) List:	Not in compliance with the inventory.
Japan ISHL Listing:	Not in compliance with the inventory.
Japan Pharmacopoeia Listing:	Not in compliance with the inventory.
Korea Existing Chemicals Inv. (KECI):	Not in compliance with the inventory.
Mexico INSQ:	Not in compliance with the inventory.
New Zealand Inventory of Chemicals:	Not in compliance with the inventory.
Philippines PICCS:	Not in compliance with the inventory.
Taiwan Chemical Substance Inventory:	Not in compliance with the inventory.
US TSCA Inventory:	On or in compliance with the inventory
EINECS, ELINCS or NLP:	Not in compliance with the inventory.

16. Other information, including date of preparation or last revision

Issue Date: 02/24/2020

Revision Information: No data available.

Version #: 1.0

Further Information: No data available.

Disclaimer: This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.