



# Multi-Purpose Lubricant

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012  
Date of issue: 01/06/2016 Revision date: 12/13/2017 Version: 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : Multi-Purpose Lubricant :  
Product code PB-50-128, PB-50-5, & 4-PB50-DB

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Multi-Purpose Lubricant.

#### 1.3. Details of the supplier of the safety data sheet

The Blaster Corporation  
8500 Sweet Valley Drive  
Valley View, Ohio 44125 - USA  
T (216) 901-5800 - F (216) 901-5801  
[www.blastercorp.com](http://www.blastercorp.com)

#### 1.4. Emergency telephone number

Emergency number : ChemTel 800-255-3924

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Flammable Liquid 4  
Aspiration toxicity 1

#### 2.2. Label elements

##### GHS-US labelling

Hazard pictograms (GHS-US) :



GHS08

Signal word (GHS-US) : Danger  
Hazard statements (GHS-US) : Combustible liquid. May be fatal if swallowed and enters airways.  
Precautionary statements (GHS-US) : Keep away from flames and hot surfaces. – No smoking. Wear protective gloves/eye protection/face protection. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

#### 2.3. Other hazards

No additional information available.

### SECTION 3: Composition/information on ingredients

#### 3.1. Substance

Not applicable.

#### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
Petroleum distillates, hydrotreated light	(CAS No) 64742-47-8	20 - 35	Flam. Liq. 3 Asp. Tox. 1
Petroleum distillates, hydrotreated light	(CAS No) 64742-47-8	20 - 35	Flam. Liq. 3 Asp. Tox. 1
Distillates, petroleum, hydrotreated light naphthenic	(CAS No) 64742-53-6	35 - 45	Asp. Tox. 1

\* The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.  
First-aid measures after skin contact : If irritation occurs, flush skin with plenty of water. Get medical attention if irritation persists.

# Multi-Purpose Lubricant

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

- First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water. Remove contact lenses, if worn. If irritation persists, get medical attention.
- First-aid measures after ingestion : Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.

### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause respiratory tract irritation.
- Symptoms/injuries after skin contact : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
- Symptoms/injuries after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
- Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

### 4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

- Suitable extinguishing media : Dry chemical. Foam. Halons.
- Unsuitable extinguishing media : Do not use carbon dioxide.

### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Combustible liquid. Products of combustion may include, and are not limited to: oxides of carbon, oxides of nitrogen.

### 5.3. Advice for firefighters

- Protection during firefighting : Keep upwind of fire. Wear full firefighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Vapours are heavier than air and may spread along floors. Use water spray to keep fire-exposed containers cool.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition.

### 6.2. Methods and material for containment and cleaning up

- For containment : Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
- Methods for cleaning up : Scoop up material and place in a disposal container. Provide ventilation.

### 6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke.
- Hygiene measures : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep locked up and out of reach of children. Keep container tightly closed and in a well-ventilated place. Keep cool.

### 7.3. Specific end use(s)

Not available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Petroleum distillates, hydrotreated light (64742-47-8)	
ACGIH	Not applicable
OSHA	Not applicable

# Multi-Purpose Lubricant

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

### Petroleum distillates, hydrotreated light (64742-47-8)

ACGIH	Not applicable
OSHA	Not applicable

### Distillates, petroleum, hydrotreated light naphthenic (64742-53-6)

ACGIH	Not applicable
OSHA	Not applicable

## 8.2. Exposure controls

Appropriate engineering controls	: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.
Hand protection	: Wear chemically resistant protective gloves.
Eye protection	: Safety glasses or goggles are recommended when using product.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Maintain levels below Community environmental protection thresholds.
Other information	: Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear
Colour	: White
Odour	: Mild aliphatic
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 193 °C (380 °F)
Flash point	: 64 °C (148 °F) (TCC)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Flammable
Vapour pressure	: < 0.5 mm Hg @ 20 °C (68 °F) <1.0 mm Hg @ 38 °C (100 °F)
Relative vapour density at 20 °C	: No data available
Relative density	: 8.2
Density	: 818 g/l @ 16 °C (60 °F)
Solubility	: No data available
Partition coefficient: n-octanol/water	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available.

# Multi-Purpose Lubricant

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2. Chemical stability

Stable under normal storage conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

#### 10.4. Conditions to avoid

Heat. Incompatible materials. Sources of ignition.

#### 10.5. Incompatible materials

Strong oxidizing agents.

#### 10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon, oxides of nitrogen.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Not classified.

All-Purpose Lubricant (liquid)	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	No data available
Petroleum distillates, hydrotreated light (64742-47-8)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	> 5.2 mg/l/4h
Distillates, petroleum, hydrotreated light naphthenic (64742-53-6)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	2.18 mg/l/4h

Skin corrosion/irritation	: Based on available data, the classification criteria are not met.
Serious eye damage/irritation	: Based on available data, the classification criteria are not met.
Respiratory or skin sensitisation	: Based on available data, the classification criteria are not met.
Germ cell mutagenicity	: Based on available data, the classification criteria are not met.
Carcinogenicity	: Based on available data, the classification criteria are not met.
Reproductive toxicity	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (single exposure)	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (repeated exposure)	: Based on available data, the classification criteria are not met.
Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/injuries after inhalation	: May cause respiratory tract irritation.
Symptoms/injuries after skin contact	: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
Symptoms/injuries after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

#### 12.2. Persistence and degradability

All-Purpose Lubricant (liquid)	
Persistence and degradability	Not established.

# Multi-Purpose Lubricant

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

### 12.3. Bioaccumulative potential

#### All-Purpose Lubricant (liquid)

Bioaccumulative potential	Not established.
---------------------------	------------------

### 12.4. Mobility in soil

No additional information available.

### 12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.

Additional information : Handle empty containers with care because residual vapours are flammable.

## SECTION 14: Transport information

In accordance with DOT

UN-No.(DOT) : NA1993

Proper Shipping Name (DOT) : Combustible liquid, n.o.s. (Petroleum distillates)

Packing group (DOT) : III

### Additional information

Other information : No supplementary information available.

Special transport precautions : Do not handle until all safety precautions have been read and understood.

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

### 15.2. US State regulations

#### All-Purpose Lubricant (liquid)

State or local regulations	This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.
----------------------------	--

## SECTION 16: Other information

Date of issue : 01/05/2016

Revision date : 12/13/2017

Other information : None.

*Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.*